


emergency overflow



**Capacity**


Organic daily load	0,84 kg BOD <sub>5</sub>
Hydraulic daily load	2,1 m <sup>3</sup>

**Water Levels**

H <sub>BB,min</sub>	1310 mm
H <sub>BB,max</sub>	1600 mm
HW <sub>ges</sub>	1750 mm
H <sub>P</sub>	600 mm
H <sub>S</sub>	1150 mm

**Dimension**

Length L	2390 mm
Width B	2190 mm
Height H	2710 mm
Inflow E	205/535 mm
Outflow A	540 mm



Maxi (as option)



<p>D Klaro E Professional 14 EW TD-Mini Carat 6500 L / 1717,1 gal.</p>			<p>Artikel-Nr. product no. article no. artículo no.</p>
<p>GB Klaro E Professional 14 inh. TD-Mini Carat 6500 L / 1717,1 gal.</p>	<p>ES Klaro E Professional 14 PE Cúpula Mini Carat 6500 L / 1717,1 gal.</p>	<p>FR Klaro E Professional 14 EH mini-dôme Carat 6500 L / 1717,1 gal.</p>	<p>revision</p>
<p>gezeichnet drawn ISC</p>	<p>Gewicht weight 265 kg</p>	<p>Otto Graf GmbH Carl-Zeiss-Str. 2-6 DE-79331 Teningen mail@graf.info www.graf.info</p>	
<p>Datum date 2016.08.16</p>	<p>Toleranz tolerance +/- 3%</p>		
<p>Maßstab scale unmaßst.</p>	<p>Einheiten units mm [inch] gal. = US gal.</p>		